

**RECEIVED
CENTRAL FAX CENTER**

JUN 10 2008

PATENT
Docket No: ST00025USU (SIRF.123USU1)
Serial No.: 09/967,136**CLAIMS**

1.(Previously presented). A method for reducing the number of calculations required to correlate an incoming spread spectrum signal received by a GPS receiver and encoded with a pseudorandom code, comprising:

determining, for the spread spectrum signal, mathematical processes that are repeated in a correlation process;

removing at least a portion of the mathematical processes that are repeated in the correlation process and results in remaining mathematical processes in the correlation process;

storing the remaining mathematical processes in a table; and

using the table during the correlation process to determine when a locally generated pseudorandom code and the incoming pseudorandom code received at the GPS receiver are correlated where the table accounts for signal phase inversion.

2.(Original) The method of claim 1, wherein the mathematical processes are partial accumulations.

3.(Original) The method of claim 2, wherein a portion of the locally generated code and a portion of the incoming pseudorandom code are used to determine correlation of the locally generated code and the incoming pseudorandom code.

4.(Original) The method of claim 3, wherein the incoming spread spectrum signal is a Satellite Positioning System (SATPS) signal.

PATENT

Docket No: ST00025USU (SIRF.123USU1)

Serial No.: 09/967,136

5.(Original) The method of claim 4, wherein the SATPS signal is a Global Positioning System (GPS) signal.

6.(Original) The method of claim 5, wherein the table is addressed using at least one data bit of the GPS signal and at least one associated code bit of the GPS signal.

7.(Original) The method of claim 6, wherein the at least one associated code bit is at least four associated code bits, and the at least one data bit is at least four data bytes.

8.(Original) The method of claim 7, wherein the data bytes are represented by In-phase (I) and Quadrature phase (Q) forms.

9-16.(Cancelled)